

## Radiator Guard Installation Instructions

Model : YZ450F  
Part No : FA-001-YA-14

Year : 2014 -

1. Remove the seat by first lifting off the fuel filler cover and removing the bolts circled in green in figure 1
2. Remove the lower radiator shrouds by removing the bolts circled in red in figure 1. Also remove the plastic radiator guards/louvers.



Figure 1: Mounting bolts for the seat and radiator shrouds

3. Remove the 2 mounting bolts from each radiator. Remove the engine brace bolts on each side circled in figure 2



Figure 2: Radiator shrouds and engine mount bolts removed

4. Bolt the radiator guards using the two radiator-to-frame bolts on each side. See figure 3
5. Install the left and right braces by fastening the engine brace bolt and the upper brace-to-radiator-guard bolt (as circled in figure 3a).



Figure 3: Fitted guards and braces, ready for the radiator shrouds to go back on

6. Refit the radiator shrouds.  
Note: they will sit more proud of the radiator due to the guards
7. Loosely fit the bolt in figure 4 circled in green (original bolt).
8. Fit the remaining bolts ensuring to use the supplied spacers on the blue circled bolt (supplied M6x25), placing the spacer in between the frame and the radiator shroud. Red bolts are M6x20 (1 original, 1 supplied with washer).



Figure 4: Refitting the radiator shrouds

9. Tighten all bolts and refit the seat.